


PICTOGRAMS




3-layer-system



Close tube after usage



Drying time 1 h



Additional notes



Cloth application



Drying time 2 h



Brush application



Curtain application



Drying time 3 h



Clean with solvent after use



Dimension Non Stable



Drying time 4 h



Clean with water after use



Dimension Semi Stable



Drying time



Cleaning by cloth



Dimension Stable



Entrance doors



Cleaning by sponge



Dipping



Exterior



Cleaning



Dry storage



Flash off


PICTOGRAMS



Flooring



Mixing ratio (2 pack) 1:2



Processing



Flowcoat application



Mixing ratio (2 pack)



Protection frost



Furniture



Mixing ratio (3 pack)
1:2:3



Protection heat



Garden furniture



Mixing ratio (3 pack)



Read documentation
before use



Interior doors



Pot life 4 h



Roll application



Interior



Pot life 6 h



Roller application



Main product
characteristics



Pot life 8 h



Roller coater application



Mixing ratio (2 pack) 1:1



Pot life



Roller sanding machine

PICTOGRAMS



Sanding (dry, manual)



Spraying by airless / airmix



UV drying



Sanding (machine)



Spraying by cup gun



Vacumat application



Sanding (manual)



Stairs



Water borne



Sanding (wet, manual)



Stirr before use



Wear gloves



Shake before use



Stirr while adding thinners e.g.



Wear respiration mask



Solvent borne (flash off)




Test color before use



Wear safety glasses



Spatula application




Usage not under +15 degrees C



Working viscosity



Spray application



Usage not under ... degrees C