

## SEDIPAN WV 007

Retarder additive



## Main product characteristics

Additive to slow down the drying during warm days or to reduce micro foam because of longer drying time (longer open time of paint film).



## Processing

## Mixing



- Add between 5 – 20% of the additive.
- Stir while adding the additive.

## Storage

- The shelf life is 36 months if the products are stored in an environment with temperature between 5 – 30°C.



## Products to use with

SEDIPAN WACP 100	SEDIPAN WACP 110	SEDIPAN WACP 200	SEDIPAN WACM 300
SEDIPAN WACM 310	SEDIPAN WACM 330	SEDIPAN WACM 400	SEDIPAN WACM 500
SEDIPAN WACM 505	SEDIPAN WACM 600	SEDIPAN WACM 640	SEDIPAN WACM 650

Don't add the additive to not listed products!



## Additional notes

## Availability

Packaging size

1l

## Where to find the MSDS



Please contact your local business Partner.

The information given at present document is not claimed to be free from error or complete. The statements and recommendations are advisory only. We don't take any responsibility to supervise the application. The applicator is fully responsible for this and its quality control. We don't accept any liability to any person for any loss damage (direct or indirect) that may arise from any use of or reliance on any of the methods or information contained in the specification for any purpose. Created on 2<sup>nd</sup> of June 2016. LG